

EPSILON

Wash-Beam 7

7*15W 5-IN-1LED Wash / Beam

User Manual



BEFORE USE, PLEASE READ THIS MANUAL.

EPSILON

Wash-Beam 7

7*15W 5-IN-1LED Wash / Beam

User Manual



BEFORE USE, PLEASE READ THIS MANUAL.

DMX Channel Values (8 channel mode)

Channel	Function	Value
1 channel	Pan	000~255
2 channel	Tilt	000~255
3 channel	Red dimmer	000~255
4 channel	Green dimmer	000~255
5 channel	Blue dimmer	000~255
6 channel	White dimmer	000~255
7 channel	Amber dimmer	000~255
8 channel	No function	000~007
	All dimmer	008~200
	Strobe from slow to fast	201~247
	Full bright	248~255

14 Channel

Channel	Function	Value
1 channel	Pan	000~255
2 channel	Pan fine	000~255
3 channel	Tilt	000~255
4channel	Tilt fine	000~255
5 channel	Pan/ Tilt speed adjustment	000~255
6 channel	Red dimmer	000~255
7channel	Green dimmer	000~255
8channel	Blue dimmer	000~255
9 channel	White dimmer	000~255
10channel	Amber dimmer	000~255
11channel	All dimmer	000~255
12channel	No function	000~009
	31 built in color macros	010~255
13channel	No function	000~009
	Strobe from slow to fast	010~255
14 channel	No function	000~127
	Sound active	128~255

Technical Specifications

Weight & Dimensions	
Depth	9.84 inches
Width	5.9 inches
Height	12.59 inches
Weight	6.5 lbs (3.8 kg)
Power	
Operating Voltage	110-240VAC, 50-60 Hertz (auto-ranging)
Fuse	5A
Power Consumption	130W
Light Source	
LED	7x15W (5-in-1) RGBWA, 60,000 hours
Optical	
Beam Angle	25 degrees
Movement Range	
Pan	540 degrees
Tilt	265 degrees
Thermal	
Max. Operating Temp.	104 degrees F (40 degrees C) ambient
Control	
Protocol	USITT DMX-512
DMX Channels	8 or 14 (User Selectable)
Input	3-pin XLR Male
Output	3-pin XLR Female
Other Information	
Available in Black Color	
Warranty	
1-year limited warranty does not cover mal-function caused by damage to LED's.	