

Intelligent Profile

Optics:

Type	Hybrid Profile
Light Source	700w LED
Average LED Life	20000 Hours
Color Temperature	6500K
CRI	> 97%
Framing	4 Independent Framing Shutters +/- 90°
Zoom	7°- 40° Linear Electronic Zoom
Frost	Linear 0 - 100%
Strobe	0 - 25Hz Times Per Second
Lens	Tempered Anti-reflective Coated Glass
Color Mixing	CMY + CTO Colormix System
Linear CTO	2700K -6500K
Color Wheel	6 Colors + Open
Gobo Wheel	8 + Open
Rotating Gobo Wheel	6 Interchangeable Glass Gobos + Open
Effect Gobo Wheel	Animation Wheel
Prism	3 Facet Prism
Prism 2	Trapezoidal Prism

Control:

Control Mode	DMX, Manual
Control Protocol	DMX, WDMX, ArtNet, sACN
RDM Support	Yes
Data In/Out	3 Pin DMX In and Out
Channels	36CHs / 52CHs
Display	Full Color 180° Reversible LCD
Movement Axis	Pan: 540°; Tilt: 270°

Specifications:

Dimensions	428x305x748mm
Weight	30.20kg
Power Connection	Powercon In + Out
Input Voltage	AC100V-240V 50/60Hz
Power Consumption	1000W Max. At Full Output
Max Heat Load	
IP Rated	